


FRAUNHOFER INSTITUTE FOR WOOD RESEARCH, WILHELM-KLAUDITZ-INSTITUT WKI



- 1 Canvas made of flax fabric.
- 2 Different hybrid fabrics.
- 3 Flax and carbon fabric.

Fraunhofer Institute for Wood Research, Wilhelm-Klauditz-Institut WKI

Application Center for Wood Fiber Research HOFZET Heisterbergallee 12 30453 Hannover Germany

Contact

Jana Winkelmann M. Sc. Telefon +49 511 9296-2820 jana.winkelmann@wki.fraunhofer.de

www.wki.fraunhofer.de

Copyright of the image material (unless stated otherwise): Fraunhofer WKI. WKI is a registered mark of the Fraunhofer-Gesellschaft. 11/2018

INNOVATIVE TECHNICAL FABRIC STRUCTURES


At the HOFZET, the application-oriented development and production of innovative, technical textiles using the latest weaving technology forms a focus of the applied research. The finished fabrics can be used, for example, as semi-finished products for a composite material or for other technical textile applications. The single or multi-layer fabrics can be applied in thermoset and thermoplastic semi-finished products and components. Crucial for this is that not only hybrid structures made from differing, conventional high-performance fibers such as carbon or glass fibers can be produced, but that requirement-meeting combinations with natural fibers and bio-based synthetic fibers can also be created. The benefits of bio-based materials in combination with conventional reinforcing fibers are thereby specifically utilized. The production of technical hybrid textiles with variable biogenic content by means of weaving technology enables the cost-effective manufacture of components with application-oriented

properties which include, in particular, outstanding mechanical and acoustic properties as well as very good crash behavior. A further very positive effect is that through the application of bio-based materials, fibers and/or polymers, the costs can be significantly reduced in some areas and the CO, balance is considerably more positive.

Manufacture of hybrid, textile semifinished products

•

By means of a double-rapier weaving machine with Jacquard attachment from the company Van de Wiele, various fabric structures can be process-adapted manufactured which are each composed of different yarn, filament or roving types. Through diverse and application-oriented combinations of materials, bond variants and fabric constructions, hybrid textile semi-finished products can be produced. With regard to a subsequent processing





into composite materials, it is possible to provide the fabric with a thermoplastic matrix yarn. Using this manufacturing technology, an outstanding impregnability, easy handling and a reduction in material consumption and process steps is achieved. In addition to the production of twodimensional hybrid tissues, this technology also enables, amongst other possibilities, three-dimensional and near-net shape fabric constructions. The diverse material selection, together with the advanced technical possibilities of the double-rapier weaving machine, offers a strong flexibility with respect to the mechanical component and performance characteristics of the manufactured semi-finished products, such as an application-specific control of the mechanical, acoustic and optical properties, as well as a reduction of the costs. Furthermore, conductive yarns or wires, which serve as sensors or conducting paths, can be directly integrated into the fabric.

Technical data

lecifical data

- Double rapier
- Jacquard attachment
- Realization of weave widths of up to 50 cm
- Creel for 3456 spools

Production possibilities for technical fabrics

- Two-dimensional fabrics
- Spacer fabrics (spacings up to 40 mm)
- Integration of matrix yarns in textile semifinished products
- Multi-layer fabrics
- Hybrid fabrics
- Function integration
- Load path-appropriate manufacture of hybrid composites

Expertize

- Development of application-specific textile semi-finished products from hybrid material systems
- Provision of cost-optimized, sustainable high-performance composite materials with the highest possible biogenic proportion
- Combination of bioplastic, natural, glass, carbon and synthetic polymer fibers
- Sustainability, recyclability

Schematic drawing of a Jacquard weaving machine.
Double-rapier weaving machine with Jacquard attachment.
Weaving machine from a different angle.